

# ELEVAH® 70

The Elevah 70 is the aerial platform equipped with a big basket, which has a capacity of 200 kg. It reaches 7 m working height.



Safety is ensured during any type of work at height (maintenance, inspection, assembly, etc ...)



The emovable control allows the platform to be raised from the ground.

## SOME ACCESSORIES AND CUSTOMISATION



**AT 10.1:** Power Batteries 12V wit Power connection to the Tractor.

➤ **OTHER ACCESSORIES AND COSTUMISATION ON P. 46**



By using stabilizers and positioning the cage 70 cm above ground level, a working height of 7 m can be reached.

ELEVAH 70

PUSH AROUND MACHINE

# ELEVAH<sup>®</sup> 70

	Without Stabilizers	With Stabilizers	
Max. working height	6 m	7,25 m	
Max capacity	200 kg		
Number of people	1		
Use	Internal		
<b>A</b>	Closed machine height	1700 mm	
<b>B</b>	Minimum platform height	380 mm	
<b>C</b>	Maximum platform height	4000 mm	5250 mm*
<b>D</b>	Base overall dimensions	1320 mm	1380 mm
<b>E</b>		780 mm	1350 mm
<b>F</b>	Cage dimensions	780 mm	
<b>G</b>		790 mm	
<b>H</b>	Max. distance from the wall	0 mm	40 mm
<b>I</b>		0 mm	300 mm
<b>J</b>	Fixed picking tray dimensions	760 mm	
<b>K</b>		420 mm	
Fixed picking tray capacity	20 kg		
Machine weight with stabilisers (power supply 220V 50/60Hz)	398 kg		
Swivel wheels dimensions (fixed)	Ø 200 x 50 mm		
Swivel wheels dimensions	Ø 150 x 45 mm		
Max. speed (rising)	0,20 m/s		
Max. speed (descending)	0,15 m/s		
<b>L</b>	Maximum pressure for wheel at full load**	2,0 kN	2,10 kN
Power supply	Lead-Acid Batteries 12V 105 Ah 200V 50/60Hz		
Battery charger	110V – 230V 50/60HZ		
Work cycles (with fresh batteries)***	200		

\* Max H. reached with cage at height -C-

\*\* Maximum pressure whereas the weight of the platform plus the maximum load on the basket are completely distributed on one side of the platform (totally asymmetric load).

\*\*\* By work cycle we mean a self-propelled movement of 20 m with a full ascent to and descent from the maximum height and with adjustment of the loading platform.



Compliant with **EN280** rule.  
Approved for outdoor use in the absence of wind.

